

# AKSESS

LOCKED VERSION

- Ductile Iron
- EN124 Class B (125kN)
- AS3996 Class B
- Unhinged
- Non-ventilated
- Hydraulic manhole cover
- New black varnish coating



Reference	Description		Mass (in kg)	Dimensions mm		
	Type	Frame		Clear Opening	Height	Frame Size
			Total			
CBAK30HFX16	Non-ventilated	Square	8.2	220 x 220	37	310
CBAK40HFX16	Non-ventilated	Square	12.8	300 x 300	37	410
CBAK45HFX16	Non-ventilated	Square	15.3	350 x 350	38	460
CBAK50HFX16	Non-ventilated	Square	18.2	400 x 400	38	510
CBAK55HFX16	Non-ventilated	Square	22.0	450 x 450	38	580
CBAK75HFX16	Non-ventilated	Rectangular	32.0	450 x 600	38	580 x 710
CBAK60HFX16	Non-ventilated	Square	29.4	500 x 500	38	610
CBAK70HFX16	Non-ventilated	Square	38.8	600 x 600	38	710
CBAK80HFX16	Non-ventilated	Square	52.7	700 x 700	41	820

The AKSESS caps symbolise four of the most common services for which manholes are used:

- Wastewater
- Storm water
- Water meters
- Lighting/Traffic lights

Each locked Aksess manhole cover is supplied with four identification caps.