

SELECTA 500 GULLY UNITS



COMPACT AND HIGH-CAPACITY

- Ductile Iron
- EN124 Class C (250kN)
- AS3996 Class D
- Hinged
- Kerb frame and grating
- Optional debris bar



2. GRATES

| Reference | Description Kerb Profile | Frame | Mass (in kg) | | | Dimensions mm | | |
|---------------------------------------|--------------------------------|-------------|--------------|---------|-------|---------------|------------|-----------------|
| | | | Total | Grating | Cover | Clear Opening | Height H/h | Frame Size (OD) |
| WITH RAISED DEBRIS BAR GRATING | | | | | | | | |
| ECSE61TF | Kerb Frame and Grate T profile | Rectangular | 54.5 | 16.5 | 14 | 385 | 205/90 | 610 x 570 |
| ECSE61SF | Kerb Frame and Grate A profile | Rectangular | 51 | 16.5 | 13 | 385 | 125/90 | 610 x 570 |
| WITH FLAT GRATING | | | | | | | | |
| ECSE61UF | Kerb Frame and Grate T profile | Rectangular | 53 | 15 | 14 | 385 | 205/90 | 610 x 570 |



ECSE61TF
SELECTA 500, T-Profile with raised selector bar grating



ECSE61SF
SELECTA 500, A-profile with raised selector bar grating



ECSE61UF
SELECTA 500 with T-profile flat grating